

Low Profile Outlet Units (BL Series)

The BL Series is the newest addition to our strong lineup. Combined with the flexibility of 15 or 20 Amps, these models are available in 2 feet through 6 feet lengths. All models are UL approved and come with a lifetime warranty. Custom units available. 20 Amp units are offered complete with 20 Amp circuit breaker, switch, wiring and duplexes.



Features

- New Sleek Design to Accommodate 15/20 AMP Receptacles or 20 Amp Duplexes
- Circuit Breaker Standard
- Metal Housing
- Snap & Slide Clip Mounting
- UL Approved UL1363 & UL60950

Model No.	Outlets	Outlet Spacing Ctr to Ctr	Electrical Rating	Cord Length	Amps	Dimensions
15 Amps - UL1363, 12 Amps - UL60950						
BL 36-10-6	10	3"	125 V, 60 Hz, 15 Amps	6'	15	36" x 2" x 1 1/4"
BL 36-10-15	10	3"	125 V, 60 Hz, 15 Amps	15'	15	36" x 2" x 1 1/4"
BL 48-12-6	12	3 1/2"	125 V, 60 Hz, 15 Amps	6'	15	48" x 2" x 1 1/4"
BL 48-12-15	12	3 1/2"	125 V, 60 Hz, 15 Amps	15'	15	48" x 2" x 1 1/4"
BL 72-15-6	15	4"	125 V, 60 Hz, 15 Amps	6'	15	72" x 2" x 1 1/4"
BL 72-15-15	15	4"	125 V, 60 Hz, 15 Amps	15'	15	72" x 2" x 1 1/4"
20 Amps units UL1363, 16 Amps UL60950						
BL 36-10-6 (20A)	10	3"	125 V, 60 Hz, 20 Amps	6'	20	36" x 2" x 1 1/4"
BL 36-10-15 (20A)	10	3"	125 V, 60 Hz, 20 Amps	15'	20	36" x 2" x 1 1/4"
BL 48-10-6 (20A)	12	3 1/2"	125 V, 60 Hz, 20 Amps	6'	20	60" x 2" x 1 1/4"
BL 60-10-15 (20A)	12	3 1/2"	125 V, 60 Hz, 20 Amps	15'	20	60" x 2" x 1 1/4"
BL 72-12-6 (20A)	15	4"	125 V, 60 Hz, 20 Amps	6'	20	72" x 2" x 1 1/4"
BL 72-12-15 (20A)	15	4"	125 V, 60 Hz, 20 Amps	15'	20	72" x 2" x 1 1/4"
Optional: Switch (S), Twist Lock (TL), Duplex (D)						
Custom units from 6" to 77" with max of 24 outlets						

