

Slim Line Series (SL Series)

Our Slim Line units are designed for those applications where space is at a premium. With their slim line stance, these units are ideal for racks, cabinets, and workbenches. The 20 Amp models are offered complete with 20 Amp circuit breaker, 20 Amp wiring, and 15/20 Amp outlets.




Features

- Push to reset Circuit Breaker
- 15Amp,UL1363 and 12 Amp UL 60950
- 20Amp,UL 1363 and 16Amp UL 60950
- UL 1363/UL 60950 Approved
- Streamlined Slim Aluminum Stance
- Grey Finish
- Spring Clip Mounting

Model No.	Outlets	Outlet Spacing Ctr to Ctr	On/Off Switch	Cord Length	Amps	Dimensions
15 Amps - UL1363, 12 Amps - UL60950						
SL 36-10-6	10	3"	No	6'	12/15	36" x 1 1/2" x 1 3/16"
SL 36-10-15	10	3"	No	15'	12/15	36" x 1 1/2" x 1 3/16"
SL 48-12-6	12	3 1/2"	No	6'	12/15	48" x 1 1/2" x 1 3/16"
SL 48-12-15	12	3 1/2"	No	15'	12/15	48" x 1 1/2" x 1 3/16"
SL 72-15-6	15	4"	No	6'	12/15	72" x 1 1/2" x 1 3/16"
SL 72-15-15	15	4"	No	15'	12/15	72" x 1 1/2" x 1 3/16"
20 Amps - UL1363, 16 Amps - UL60950						
SL 36-10-6 (20A)	10	3"	No	6'	16/20	36" x 1 1/2" x 1 3/16"
SL 36-10-15 (20A)	10	3"	No	15'	16/20	36" x 1 1/2" x 1 3/16"
SL 48-12-6 (20A)	12	3 1/2"	No	6'	16/20	48" x 1 1/2" x 1 3/16"
SL 48-12-15 (20A)	12	3 1/2"	No	15'	16/20	48" x 1 1/2" x 1 3/16"
SL 72-15-6 (20A)	15	4"	No	6'	16/20	72" x 1 1/2" x 1 3/16"
SL 72-15-15 (20A)	15	4"	No	15'	16/20	72" x 1 1/2" x 1 3/16"

Optional: Switch (S), Twist Lock (TL)

Custom units from 6" to 77" with max of 24 outlets



'X' MAY VARY FROM
6 INCHES TO 77 INCHES